

DECLARATION OF PERFORMANCE

DoP HI – 144/23-01

according to REGULATION (EU) No 305/2011 (Article 4 and Annex III)
laying down harmonized conditions for the marketing of construction products

Unique identification code of the product-type:

IZOTEKT REFLEX P5 APAO

**APAO bitumen sheet with polyester fleece reinforcement: 7,5 m x 1 m x 5,2 mm
Surface protection: mineral granules / polymeric sheeting**

Intended use:

**APAO bitumen sheet used as top layer in multilayer systems
without permanent heavy surface protection (EN 13707)**

Manufacturer:

FRAGMAT TIM d.o.o., Spodnja Rečica 77, SI-3270 Laško

Systems of AVCP:

System 2+

Harmonized standard:

EN 13707:2004+A2:2009

Notified body:

1404 - ZAVOD ZA GRADBENIŠTVO SLOVENIJE, Dimičeva 12, 1000 LJUBLJANA

Declared performances:

| Essential characteristics: | Performance | | | Harmonized technical specification |
|---|-----------------------|---------|-------------------|------------------------------------|
| | EN method | Unit | Value | |
| Water tightness | 1928 | kPa | ≥ 400 | |
| Flexibility at low temperature | 1109 | °C | ≤ -25 | |
| Resistance to tearing • longitudinal • transversal | 12310-1 | N | * NPD * NPD | |
| Shear resistance of joints • longitudinal • transversal | 12317-1 | N/50 mm | * NPD * NPD | |
| Reaction to fire | 13501-1 | class | E | |
| External fire performance | 13501-5 | class | F _{ROOF} | |
| Resistance to static loading | 12730/A | kg | * NPD | |
| Resistance to impact | 12691/A | mm | * NPD | |
| Tensile properties • longitudinal • transversal | 12311-1 | N/50mm | ≥ 780 ≥ 630 | EN 13707:2004+A2:2009 |
| Elongation • longitudinal • transversal | 12311-1 | %/50mm | ≥ 35,0 ≥ 35,0 | |
| Resistance to root penetration | 13948 | - | * NPD | |
| Flexibility at low temperature after artificial ageing by long term exposure to elevated temperature (12 weeks at 70°C) | 1296/1109 | °C | * NPD | |
| Flow resistance at elevated temperature after artificial aging by long term exposure to elevated temperature (12 weeks at 70°C) | 1296/1110 | °C | ≥ 140°C | |
| Chemical resistance | 1847/13707 Annex C | - | pass | |
| Content of dangerous substances | Annex ZA | / | no | |

* NPD – no performance determined

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Laško, 20.01.2023

Head of production:

Marko Mavri